

## ZKD104A / ZKD108A



## Specification

Model		ZKD104A	ZKD108A
Video/Audio input	Video compression	H.264	
	Analog and HD-TVI video input	4-ch	8-ch
		BNC interface (1.0Vp-p, 75 Ω)	
	Supported camera types	720P/25, 720P/30, CVBS	
	Audio compression	G.711u	
Audio input / Two-way audio in	1-ch, RCA (2.0 Vp-p, 1 KΩ)		
Video/Audio output	HDMI / VGA output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz	
	Encoding resolution	Main stream: 720P (Non real time) / WD1 / 4CIF / VGA / CIF	
		Sub-stream: CIF / QVGA / QCIF	
	Frame rate	Main stream: 1/16 fps ~ Real time frame rate	
		Sub-stream: 1/16 fps ~ Real time frame rate	
	Video bitrate	32 Kbps ~ 6 Mbps	
	Audio output	1-ch, RCA (Linear, 1KΩ)	
	Audio bitrate	64 Kbps	
	Dual-stream	Support	
	Stream type	Video, Video & Audio	
Synchronous playback	4-ch	8-ch	
Playback resolution	720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF		
Network management	Remote connections	128	
	Network protocols	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS	
Hard disk	SATA	1 SATA interface	
	Capacity	Up to 6 TB capacity for each disk	
External interface	Network interface	1; 10M / 100M self-adaptive Ethernet interface	
	USB port	2 × USB2.0	
General	Power supply	12V DC	
	Consumption (without hard disks)	≤ 8W	≤ 12W
	Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)	
	Working humidity	10% ~ 90%	
	Dimensions (W × D × H)	200 × 200 × 45mm (7.9 × 7.9 × 1.8 inch)	
Weight (without hard disks)	≤ 0.8 kg / 1.8 lb		