

acebook

#### : 203.66.45.240/seo/facebook

# **AVM302A**







Card













#### 1.3 MP IP Camera

## O FEATURES

- Easy network setup with your iPhone / iPad
- 1.3 Megapixel with HDTV 720p quality, allowing users to notice minor details more easily
- ONVIF (OnvifS) standard supported to simplify system integration
- External alarm I/O device connection



- Micro SD card support (up to 64GB) for video storage
- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- Microphone built-in for audio recording
- Remote Surveillance
  - -- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
  - -- Push Video available on your iOS and Android devices when used with Push Video NVR series.

## O SPECIFICATIONS

Network	
Network Compression	H.264 / MPEG4 / MJPEG
Multiple Video Streaming	3 (H.264, MJPEG, MPEG4)
(Encode Modes, IPS, Resolution)	
LAN Port	YES
LAN Speed	10/100 Based-T Ethernet
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP,
	ICMP, SMTP, FTP, HTTP, RTP, RTSP, UPnP
ONVIF Compatible	YES (Profile S)
Frame Rate	NTSC: 30, PAL: 25
Number of Online Users	10
Security	(1) Multiple user access levels with password
	(2) IP address filtering
	(3) Digest authentication
Remote Access	(1) Internet Explorer on Windows operating system
	(2) 16CH Video Viewer on Windows & MAC operating system
	(3) EagleEyes on iPhone, iPad & Android mobile devices



### **•** SPECIFICATIONS (CONTINUED)

nage Sensor ideo Resolution	1/4" SONY CMOS image sensor
	SXGA, 720P, VGA, QVGA
lin Illumination	0.1 Lux / F1.5
hutter Speed	1/2 to 1/10,000 sec
/N Ratio	More than 48dB (AGC off)
ens	f3.8mm / F1.5
iewing Angle	62.7° (Diagonal) / 53.7° (Horizontal) / 34.1° (Vertical)
Vhite Balance	ATW
GC	Auto
RIS Mode	AES
PIR Sensor	Detection Range 76° wide angle with up to 6m long distance
	at 2m height (under 30°C)
licro SD Card Slot	YES (up to 64GB)
xternal Alarm I/O	YES
licrophone	YES
ower Source (±10%)	12V / 1A
current Consumption (±10%)	0.25A
ower Consumption (±10%)	3.75W (PoE) ; 3.75W (PoN) ; 3W (DC Adapter)
Operating Temperature	0°C ~40°C
Others	
lobile Surveillance	iPad / iPhone / Android mobile device
OE (Power-over-Ethernet)	YES (IEEE 802.3af)
TC (real-time clock)	YES
lotion Detection	YES
igital Pan / Tilt / Zoom	YES
vent Notification	FTP / Email
/inimum Web Browsing Requirements	<ul> <li>Intel core i3 or higher, or equivalent AMD</li> <li>2GB RAM</li> <li>AGP graphics card, Direct Draw, 32MB RAM</li> <li>Windows 7, Vista &amp; XP, DirectX 9.0 or later</li> </ul>

\* The specifications are subject to change without notice.





EagleEyes for Mobile Surveillance Official Website : www.eagleeyescctv.com Video Demo : 203.66.45.240/seo/Video Facebook : 203.66.45.240/seo/facebook

#### **O** DIMENSION

